

2.10 PRIMAFLEX PVC 3000S

Temperature range -30 °C bis 100 °C



Description

Simple, highly flexible spiral hoses in lightweight version made of very thin-walled PVC with wide-meshed polyester fabric reinforcement (3000 L) or in reinforced but still lightweight version made of PVC-coated polyester fabric (3000 S) with spiral.

Suitable for conveying gaseous media.

Available in our online shop

Properties

- Low-priced
- Lightweight
- Highly compressible
- Highly flame-retardant
- Wall thickness: 0.25 mm

Application ranges

Ventilation, Ventilation, Suction technology, PVC hoses, Exhaust air systems, Fan hose, Ventilation technology, Air-conditioning and ventilation technology, Kitchen range hood, , Drying of buildings

Length

Standard lengths: 10m - 20m

TECHNICAL SPECIFICATIONS

Inner-Ø (mm)	Bending radius (mm)	Pressure (bar)	Vacuum (bar)	Weight (kg/m)	Length (m)	Article-No.
50	35	0,8	0,2	0,13	10 - 20	6012051
63	42	0,8	0,16	0,17	10 - 20	6012060
70	49	0,7	0,14	0,2	10 - 20	6012070
76	53	0,6	0,1	0,22	10 - 20	6012076
80	56	0,6	0,1	0,24	10 - 20	6012080
102	70	0,5	0,09	0,31	10 - 20	6012102
127	88	0,5	0,08	0,38	10 - 20	6012127
152	105	0,5	0,06	0,45	10 - 20	6012152
180	130	0,2	0,05	0,65	10 - 20	6012180
203	140	0,2	0,05	0,73	10 - 20	6012203
254	175	0,1	0,04	0,92	10 - 20	6012254
305	210	0,06	0,03	1,11	10 - 20	6012305
357	245	0,05	0,02	1,3	10 - 20	6012357
408	280	0,04	0,02	1,5	10 - 20	6012408
510	350	0,02	0,01	1,9	10 - 20	6012510